



MATERIAL SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product name: Tangit PVC-C

Product-Code: 417378

Supplier:

HENKEL AUSTRALIA PTY. LIMITED
ADHESIVE TECHNOLOGIES
135-141 Canterbury Road
3137 Kilsyth, Victoria

Australia

Phone: +61 (3) 9724 6444

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

SECTION 2. HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE:

Hazardous according to the criteria of ASCC.

Classification of material F - Highly flammable Xi - Irritant

Risk phrases:

R11 Highly flammable.
R36/37 Irritating to eyes and respiratory system.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

Safety phrases:

S2 Keep out of the reach of children.
S16 Keep away from sources of ignition - No smoking.
S25 Avoid contact with eyes.
S33 Take precautionary measures against static discharges.
S46 If swallowed, seek medical advice immediately and show this container or label.
S51 Use only in well-ventilated areas.

Dangerous Goods information:

Classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Signal word:

None



MATERIAL SAFETY DATA SHEET

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

General chemical description:

Non-plasticized PVC
in a mixture of organic solvents

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Tetrahydrofuran	109-99-9	> 30 %
Butanone	78-93-3	10 - < 25 %
Cyclohexanone	108-94-1	< 15 %

SECTION 4. FIRST AID MEASURES

Ingestion:	Rinse mouth, do not induce vomiting, consult a doctor.
Skin:	Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.
Eyes:	Immediately flush eyes with soft jet of water or eye rinse solution for at least 5 minutes. If pains remains (intensive smarting, sensitivity to light, visual disturbance) continue flushing and contact/seek doctor or hospital.
Inhalation:	Move to fresh air, consult doctor if complaint persists.
Medical attention and special treatment:	Treat symptomatically.
First Aid facilities:	Eye wash Normal washroom facilities

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media:	carbon dioxide, foam, powder, water spray jet, fine water spray
Improper extinguishing agent:	High pressure waterjet
Particular danger in case of fire:	In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO ₂) can be released. Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.
Special protective equipment for fire-fighters:	Wear protective equipment. Wear self-contained breathing apparatus.
Additional fire fighting advice:	Cool endangered containers with water spray jet.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions and emergency procedures:	Wear protective equipment. Ensure adequate ventilation. Keep away from sources of ignition. Danger of slipping on spilled product.
---	---



MATERIAL SAFETY DATA SHEET

Environmental precautions: Do not empty into drains / surface water / ground water.

Clean-up methods: Remove with liquid-absorbing material (sand, peat, sawdust).
Dispose of contaminated material as waste according to Chapter 13.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling: Ventilate working rooms thoroughly. Avoid naked flames, sparking and sources of ignition. Switch off electrical devices. Do not smoke, do not weld. Do not empty waste into waste water drains.
Also to be noted when processing larger amounts (> 1 kg): during processing and drying after adhesion, ventilate well. Avoid all sources of fire such as stoves and ovens. Switch off all electrical devices such as parabolic heaters, hot plates, storage heaters etc. in good time for them to have cooled down before commencing work. Avoid all sparks, including those occurring at electrical switches and devices.

Conditions for safe storage: Store in sealed original container.
Close the container carefully after use and store it at a good ventilated place.
Ensure adequate ventilation.
Temperatures between + 5 °C and + 35 °C
Do not store together with oxidants.
Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National exposure standards:

Ingredient	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
TETRAHYDROFURAN 109-99-9		100	295	-	-	-
METHYL ETHYL KETONE (MEK) 78-93-3		150	445	-	-	-
		-	-	-	300	890
CYCLOHEXANONE 108-94-1		25	100	-	-	-

Eye protection: Goggles which can be tightly sealed.

Skin protection: Suitable protective clothing
Nitrile rubber gloves should be worn.

Respiratory protection: If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Whitish, opaque
free-flowing

Odor: pronounced individual odour, intensive, sweet

Flash point: -16 °C (3.2 °F)

Density: 0.981 g/cm³

Solubility: Solvent: Water, Partially soluble



MATERIAL SAFETY DATA SHEET

SECTION 10. STABILITY AND REACTIVITY

Stability:	Stable under recommended storage conditions.
Conditions to avoid:	Take measures to prevent the build-up of electrostatic charges. Heat, flames, sparks and other sources of ignition.
Incompatible materials:	Reaction with strong bases Reaction with oxidants. Reaction with metal halides.
Hazardous decomposition products:	Oxides of carbon. Irritating and toxic gases or fumes may be released during a fire.

SECTION 11. TOXICOLOGICAL INFORMATION

HEALTH EFFECTS:

Ingestion:	May cause central nervous system effects, such as headache, nausea, vomiting, abdominal pain, dizziness, confusion, and breathing difficulties.
Skin:	May cause mild skin irritation. Repeated exposure may cause skin dryness or cracking.
Eyes:	This product is irritating to the eyes.
Inhalation:	Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.

Toxicity data:

Acute oral toxicity:	Tetrahydrofurane	LD 50 (Rat) = 1,650 mg/kg
	109-99-9	
	Methyl ethyl ketone	LD 50 (Mouse) = 670 mg/kg
	78-93-3	LD 50 (Rat) = 2,300 - 3,500 mg/kg LD 50 (Rat) = 4,500 - 6,800 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

General ecological information:	Do not empty into drains / surface water / ground water.
--	--

SECTION 13. DISPOSAL CONSIDERATIONS

Waste disposal of product:	Collection and delivery to recycling enterprise or other registered elimination institution.
Disposal for uncleaned package:	Use packages for recycling only when totally empty.



MATERIAL SAFETY DATA SHEET

SECTION 14. TRANSPORT INFORMATION

Road and Rail Transport:

Dangerous Goods information: Classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

UN no.: 1133
Proper shipping name: ADHESIVES
Class or division: 3
Packaging group: II
Emergency information: Refer to the Dangerous Goods - Initial Emergency Response Guide HB 76.
EPG: 3A1

Marine transport IMDG:

UN no.: 1133
Proper shipping name: ADHESIVES
Class or division: 3
Packaging group: II
EmS: F-E ,S-D
Seawater pollutant: -

Air transport IATA:

UN no.: 1133
Proper shipping name: Adhesives
Class or division: 3
Packaging group: II
Packaging instructions (passenger): 353
Packaging instructions (cargo): 364

SECTION 15. REGULATORY INFORMATION

SUSDP Poisons Schedule: None

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms: ASCC - Australian Safety and Compensation Council
SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons
STEL - Short term exposure limit
TWA - Time weighted average

Reason of change: Reviewed MSDS. Reissued with new date. involved chapters: 1-16

Date of previous issue: 19.05.2011

Disclaimer:



MATERIAL SAFETY DATA SHEET

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material. The information contained in this Material Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Material Safety Data Sheet. This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.